

### FEATURES

- High Voltage Operation : VDS=50V
- High Power : 45.0dBm (typ.) @ Psat
- Power Gain : 19dB (typ.) @ f=2.14GHz
- Proven Reliability

### DESCRIPTION

SEI's GaN-HEMT offers high efficiency, ease of matching, greater consistency and broad bandwidth for high power L-band amplifiers with 50V operation, and gives you higher gain.

This new product is ideally suited for use in 2.1GHz W-CDMA and LTE design requirements as it offers high gain, long term reliability and ease of use.



### ABSOLUTE MAXIMUM RATINGS ( Case Temperature Tc=25deg.C )

Item	Symbol	Condition	Rating	Unit
Operating Voltage	VDS		55	V
Drain-Source Voltage	VDS	VGS=-8V	160	V
Gate-Source Voltage	VGS		-15	V
Total Power Dissipation	Pt		37.5	W
Storage Temperature	Tstg		-65 to +175	deg.C
Channel Temperature	Tch		250	deg.C

### RECOMMENDED OPERATING CONDITION

Item	Symbol	Condition	Limit	Unit
DC Input Voltage	VDS		≤ 55	V
Forward Gate Current	IGF	RG=15ohm	≤ 69	mA
Reverse Gate Current	IGR	RG=15ohm	≥ -1.1	mA
Channel Temperature	Tch		≤ 180	deg.C
Average Output Power	Pave.		≤ 42.0	dBm

### ELECTRICAL CHARACTERISTICS ( Case Temperature Tc=25deg.C )

Item	Symbol	Condition	Limit			Unit
			Min.	Typ.	Max.	
Pinch-Off Voltage	Vp	VDS=50V, IDS=7.8mA	-1.0	-1.5	-2.0	V
Saturated Power	Psat *1	VDS=50V	44.0	45.0	-	dBm
Drain Efficiency	ηd *2	IDS(DC)=150mA	10.5	12.5	-	%
Power Gain	Gp *2	f=2.14GHz	18.0	19.0	-	dB
Thermal Resistance	Rth	Channel to Case at 24W PDC	-	5.0	6.0	deg.C/W

\*1 : 10%-duty RF pulse ( DC supply constant )


\*2 : Pout=31.5dBm, CW

RoHS COMPLIANCE	Yes
-----------------	-----




S-Parameters @VDS=50V, IDS(DC)=150mA, f=0.5 to 5.5GHz  
 ZI = Zs = 50ohm Marker : 2.14GHz


- Reference DATA -



Freq. GHz	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.50	0.92	-167.76	11.88	67.33	0.007	-1.05	0.52	-71.31
0.60	0.91	-172.44	9.91	60.12	0.008	-9.94	0.55	-79.39
0.70	0.91	-176.35	8.50	53.22	0.007	-8.07	0.57	-87.12
0.80	0.91	-179.64	7.40	46.87	0.007	-10.93	0.60	-94.46
0.90	0.90	-177.22	6.61	39.83	0.007	-8.43	0.62	-101.38
1.00	0.90	-174.37	5.93	34.28	0.007	-5.18	0.65	-107.51
1.10	0.90	-172.14	5.46	28.05	0.006	-8.73	0.68	-112.74
1.20	0.89	-169.65	5.09	22.56	0.006	-11.64	0.70	-117.63
1.30	0.88	-167.20	4.78	16.88	0.005	-8.15	0.71	-122.04
1.40	0.88	-164.80	4.53	10.93	0.006	3.38	0.73	-126.03
1.50	0.87	-162.30	4.38	4.93	0.007	7.18	0.75	-129.81
1.60	0.85	-160.12	4.27	-1.03	0.007	-0.84	0.77	-133.16
1.70	0.84	-157.53	4.21	-7.87	0.007	7.36	0.79	-136.27
1.80	0.81	-155.22	4.21	-14.31	0.008	2.46	0.80	-139.10
1.90	0.78	-152.62	4.27	-22.78	0.008	5.59	0.82	-141.54
2.00	0.73	-150.55	4.35	-31.36	0.008	-2.59	0.84	-144.10
2.10	0.67	-149.70	4.49	-41.55	0.010	-6.62	0.86	-145.87
2.20	0.60	-150.44	4.58	-53.44	0.011	-17.62	0.90	-148.41
2.30	0.54	-156.11	4.58	-68.01	0.011	-26.30	0.92	-151.11
2.40	0.52	-165.55	4.47	-82.96	0.011	-34.31	0.95	-153.98
2.50	0.57	-174.45	4.09	-100.02	0.012	-53.88	0.97	-157.62
2.60	0.66	-177.90	3.58	-115.25	0.009	-67.79	0.97	-161.15
2.70	0.75	-177.13	3.04	-128.27	0.008	-87.49	0.97	-164.01
2.80	0.81	-174.57	2.53	-138.81	0.006	-89.61	0.96	-166.41
2.90	0.86	-171.89	2.14	-148.70	0.005	-103.89	0.96	-168.36
3.00	0.89	-168.51	1.79	-155.37	0.004	-137.30	0.95	-170.12
3.10	0.91	-166.09	1.53	-162.57	0.003	-132.30	0.95	-171.70
3.20	0.93	-163.76	1.32	-167.51	0.002	171.39	0.94	-173.24
3.30	0.94	-160.96	1.15	-172.75	0.003	-179.32	0.94	-174.55
3.40	0.94	-158.76	1.01	-177.44	0.003	139.32	0.94	-175.89
3.50	0.95	-156.39	0.90	-178.06	0.003	132.52	0.93	-177.18
3.60	0.95	-154.54	0.81	-175.02	0.005	127.36	0.93	-178.48
3.70	0.95	-152.38	0.73	-170.36	0.005	122.70	0.93	-179.59
3.80	0.95	-150.32	0.68	-167.48	0.006	112.99	0.93	-179.18
3.90	0.95	-147.92	0.63	-163.44	0.007	102.76	0.92	-177.96
4.00	0.95	-145.49	0.58	-160.11	0.009	106.05	0.92	-176.76
4.10	0.95	-143.02	0.56	-156.87	0.010	95.65	0.92	-175.67
4.20	0.95	-140.18	0.52	-152.60	0.011	87.44	0.91	-174.45
4.30	0.95	-137.45	0.51	-149.28	0.013	86.12	0.91	-173.35
4.40	0.95	-133.74	0.49	-145.93	0.015	77.51	0.91	-172.11
4.50	0.95	-129.79	0.48	-140.55	0.017	73.28	0.91	-170.84
4.60	0.95	-124.99	0.48	-136.95	0.020	66.34	0.90	-169.42
4.70	0.95	-120.07	0.48	-131.34	0.021	58.68	0.90	-168.05
4.80	0.95	-113.93	0.48	-126.35	0.024	52.95	0.90	-166.61
4.90	0.95	-106.51	0.50	-120.05	0.027	44.93	0.89	-165.05
5.00	0.95	-97.54	0.50	-113.46	0.031	37.57	0.89	-163.57
5.10	0.95	-86.55	0.53	-105.86	0.036	28.40	0.88	-161.77
5.20	0.95	-73.45	0.55	-96.22	0.041	19.22	0.87	-160.12
5.30	0.95	-56.67	0.57	-85.88	0.047	7.98	0.86	-158.23
5.40	0.94	-37.29	0.60	-71.99	0.053	-4.75	0.85	-156.31
5.50	0.95	-13.73	0.60	-58.10	0.060	-19.80	0.83	-154.40



**MTTF Calculation  
- Estimated MTTF -**



**Ea=1.6eV  
Confidence Level=90%**

Channel Temp. ( deg.C )	MTTF ( Hours )
160	4.05 x 10 <sup>7</sup>
180	6.07 x 10 <sup>6</sup>
200	1.07 x 10 <sup>6</sup>

$$AF = \exp\left[\frac{-Ea}{k}\left(\frac{1}{T_{stress}} - \frac{1}{T_{use}}\right)\right]$$

$$MTTF_{use} = MTTF_{stress} \times AF$$

Where;

AF : acceleration factor

Ea : activation energy (1.6eV)

k : Boltzmann's constant (8.62x10<sup>-5</sup>eV/K)


T<sub>stress</sub> : stress temperature (K)

T<sub>use</sub> : use temperature (K)

### ESD characteristic

Test Methodology	Class
Human Body Model (per JESD22-A114)	0
Machine Model (per JEIA/ESD22-A115)	A

### MK Package Outline Metal-Ceramic Hermetic Package





# **EGN21C030MK**

***High Voltage - High Power GaN-HEMT***

**For further information please contact:**

**<http://global-sei.com/Electro-optic/about/office.html>**